

Thoroughbred

Heavy-Duty Floor Machine



Super durable and built to be the best, the Thoroughbred is precision balanced for maximum cleaning efficiency and reduced operator fatigue.

- The heavy-duty dual capacitor, 66-frame motor, partnered with a precision gear train, give the Thoroughbred the balance, dependability and power necessary to tackle any job.
- A straight-line, high torque 11:1 planetary gear system provides efficient transfer of power from the motor to the driver, assuring smooth and quiet operation.
- The Thoroughbred features an ergonomically angled handle with a mechanical lock-out. This safety feature helps prevent unauthorized operation.
- The heavy-duty polished aluminum motor mount and skirt castings provide a solid foundation for years of trouble-free service. It's just one reason the Thoroughbred is covered by a 7-year limited warranty.
- Thoroughbreds are available with a 1 or 1.5 HP motor and in 17-in. and 20-in. widths to match any floor care need.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com

Thoroughbred Specifications

| | | | | | |
|--|--|---|--|---|--|
| Pad Size | 17 in. (43.2 cm) 20 in. (50.8 cm) | Overload Protection | 20-amp circuit breaker | Weight -Machine • 17 in. 1 HP • 20 in. 1 HP • 20 in. 1.5 HP | 94 lbs. (42.6 kg) 101 lbs. (46 kg) 115 lbs. (52.2 kg) |
| Motor -HP -Speed -Type -Voltage | 1 HP or 1.5 HP 1700 RPM 66-Frame, dual capacitor 110-120V. 220-240V. available | Gearbox -1 HP -1.5 HP | 11:1 ratio 2-idler planetary gear 3-idler planetary gear | | |
| Current -1 HP -1.5 HP | 12.6 amp @ 120V. 6.8 amp @ 240V. 15 amp @ 120V. 8.3 amp @ 240V. | Cord | 50 ft. (15.25 m), 14-3 SJT Safety yellow | -Shipping • 17 in. 1 HP • 20 in. 1 HP • 20 in. 1.5 HP | 106 lbs. (48 kg) 115 lbs. (52.2 kg) 129 lbs. (58.5 kg) |
| | | Wheels | 5 in. (12.7 cm) non-marking | | |
| | | Sound Level | 68 dBA | Warranty | 7 year limited |
| | | Dimensions Length Width Height | 24 in. (61 cm) 21 in. (53 cm) 18 in. (46 cm) 49 in. (124 cm) | | |
| Productivity — Measured in square feet per hour. | | | | | |
| | Polish | Scrub | Shampoo | Spray Buff | |
| Thoroughbred 17" | 4,400 | 2,700 | 1,200 | 1,900 | |
| Thoroughbred 20" | 6,300 | 3,600 | 1,430 | 2,100 | |

1 Dual switch levers allow operator to easily control the side-to-side movement of the machine.

2 Heavy duty metal strain relief and internal compression lock keep the cord secure.



4-Gallon Solution Tank

This optional solution tank is easily attached to the machine handle—no tools necessary.

3 Built-in cord wrap hook provides easy storage for the power cord.

4 The polished aluminum skirt casting stabilizes the machine, maximizing cleaning efficiency.

5 360° non-marking bumper protects walls and fixtures from accidental damage.

11 Safety lock-out lever helps prevent unauthorized use of the machine.


10 Sturdy 1.5-in. tube handle is chrome plated to resist corrosion.

9 Heat-treated, aircraft-grade aluminum tube clamp holds the handle firmly in place during operation.

8 Precision-cast aluminum locking lever lets operator adjust handle to a comfortable position.

7 Heavy, polished aluminum motor mount casting provides a solid foundation, assuring smooth operation.

6 5-in. rear transport wheels make the Thoroughbred easy to move.



NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958 USA
800/677-1663 or 419/531-2121
Fax 419/531-3761
www.nss.com
mailus@nss.com
Specifications and appearance
subject to change without notice.

DISTRIBUTED BY