



Colt Series

Heavy-Duty Cord-Electric Wet/Dry Vacuums



The Colt Series of wet/dry vacuums from NSS® offers incredible cleaning power and versatility. Available in three different sizes, the Colt vacuums allow you to match the machine with your requirements:

Colt 1450 P

- 14.5-gallon recovery capacity
- Rotocast polyethylene tank with ten-year limited warranty
- Tip-dispose base for emptying convenience

Colt 1250 S

- 12.5-gallon recovery capacity
- High grade stainless steel tank with three-year limited warranty
- Tip-dispose base for emptying convenience

Colt 800 P

- 8-gallon recovery capacity
- Rotocast polyethylene tank with ten-year limited warranty
- Drain plug for easy emptying




NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com

- 1.23 HP, 2-stage bypass vacuum motor provides powerful suction for any cleaning job, wet or dry. A separate stream of fresh air cools the motor, preventing damage from moisture and debris.
- Durable Colt powerheads incorporate narrow openings and large chambers to reduce motor noise, just like a car muffler. The result is a quiet 62 dbA sound level, allowing you to use a Colt day or night in occupied areas with minimal disruption to co-workers, customers, or patients.
- Dependable, heavy-duty Colt vacuums are ideal for wet and dry spill pick-up as well as stripping solution recovery in schools, healthcare facilities, hotels, and retail locations.
- For added productivity, a 27-inch front mount squeegee is available.

Colt Cord-Electric Specifications

Motor -Type	1.23 HP, 2-stage bypass, 110-120V. 220-240V. available	Construction -Tank	Rotocast polyethylene 304 stainless, 22 gauge	Sound Level	62 dbA @ operator
-Air Flow -Waterlift	92 CFM (2.6 m ³) 84 in. (215 cm)	• Colt 800 P • Colt 1250 S • Colt 1450 P	Rotocast Polyethylene Rotocast Polyethylene	Cord	35 ft. (9 m) 18-3 SJTWA
Front Mount Squeegee	Available 27" toe-operated assembly with two urethane blades	-Powerhead -Base	Polyethylene Tip dispose polyethylene Tip dispose polyethylene	Weight -Machine	
Capacity -Recovery		• Colt 800 P • Colt 1250 S • Colt 1450 P	10-in. (25.4 cm) chemical- resistant	• Colt 800 P • Colt 1250 S • Colt 1450 P	46 lbs. (20.9 kg) 63 lbs. (38.6 kg) 62 lbs. (38.1 kg)
• Colt 800 P • Colt 1250 S • Colt 1450 P	8 gal. (30.3 l.) 12.5 gal. (47.5 l.) 14.5 gal. (55 l.)	-Wheels	3-in. (7.5 cm) chemical resistant	-Shipping	22 lbs. (9.9 kg)
-Tank		-Casters		• Colt 800 P • Colt 1250 S • Colt 1450 P	52 lbs. (23.6 kg) 90 lbs. (40.8 kg) 89 lbs. (40.4 kg)
• Colt 800 P • Colt 1250 S • Colt 1450 P	17.5 gal. (66.0 l.) 22 gal. (83.0 l.) 24 gal. (91.0 l.)	Filtration System	Dynel filter 625 in. ² (.4 m ²) HEPA filter assembly available	• Powerhead	30 lbs. (13.6 kg)
		-Material		Shipping Class	150
		-Area		Warranty	3 years limited 10 years poly parts
		-HEPA			



To quiet motor noise, suction air (black arrows) is squeezed through narrow openings and released into larger chambers within the powerhead—much like a car's muffler. A separate stream of clean, fresh air (gray arrows) cools the motor, protecting it from moisture and debris.



Tip-dispose bases empty easily into any drain up to toilet height.

1 Rugged polyethylene powerhead and base stand up to heavy-duty commercial use.

5 Tip-dispose tank (and drain on the Colt 800) allows easy emptying into most toilets and drains.

2 An optional HEPA filter assembly is available.

3 Optional 27-in. front mount squeegee is ideal for spill recovery in large areas.

4 Large rear wheels and front casters make the Colt extremely maneuverable.



The optional HEPA filter provides additional protection for healthcare and other applications where Indoor Air Quality is a major concern.



NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958 USA
419/531-2121 or 800/677-1663
Fax 419/531-3761
www.nss.com
mailus@nss.com
Specifications subject to change without notice.

DISTRIBUTED BY